



## Skirting Board (RL)

The WARCO Skirting Board is a resilient baseboard made of rubber granulate, adhered to the wall at floor level. It conceals cut edges, covers gaps up to 1.5 cm wide and creates a neat transition between floor and wall.

At the same time it protects the wall from scuffs and splash marks during mopping or vacuuming. Thanks to its flexibility it follows gentle curves cleanly. With a stepped rebate joint and rounded top edge, adjoining lengths form a continuous, functional and decorative wall finish.

### Product data

Colour	<b>Travertine</b>	Weight	<b>1.2 kg/Piece = 1.6 kg/lin. m</b>
Installation	<b>Permanent elastic bonding RL</b>	Conversion	<b>1 lin. m = 1.33 Piece</b>
Packaging	<b>750 x 20 x 80 mm</b>	Useful size	<b>750 x 20 x 80 mm</b>

## Properties



### Colour Travertine

The Travertine colour is characterised by a harmonious combination of soft beige tones and subtle dark accents that evoke the natural colouring of travertine stone. This colour gives the surface a warm, earthy and elegant appearance. "Travertine" is a neutral colour scheme that fits seamlessly into both modern and traditional environments. It creates a sophisticated yet inviting atmosphere. The material used - virgin, non-toxic EPDM rubber granules - is UV-resistant and colour-fast over time.




### Material

The product is manufactured from high quality coloured EPDM rubber granules. UV-stabilised polyurethane is used as a binder. EPDM (ethylene-propylene-diene rubber) is a synthetic rubber that is naturally highly UV resistant, stable over a wide temperature range and resistant to many chemicals. Only virgin, pollution-free EPDM rubber granules have been used in the manufacture of this product. EPDM is known for its exceptionally long life and high durability.



### Installation

The wall strip has a flat underside which is bonded to a suitable substrate. Bonding can be full-surface or spot, depending on the characteristics of the substrate. Use WARCO's permanently elastic PU adhesive or an equivalent product. The step-jointed edges of the tapes fit closely together during installation, resulting in a clean and neat appearance.



### Structure of the underside

The product has a smooth, consistently even underside without embossed structural elements or drainage channels. It rests fully on the sub-base. If necessary, adequate drainage must be ensured through appropriate measures. Installation is carried out on a suitable, level, and permanently load-bearing sub-base. Please refer to the installation guidelines for correct application.

## Skirting Board (RL)

### Characteristics



#### Cfl-s1

Fire behaviour according to EN 13501-1: Cfl-s1  
Limited contribution to fire – Low smoke emission



#### Indoor & Outdoor

Weather and frost resistant – suitable  
for versatile indoor and outdoor use.



#### Colourfast and UV-resistant

The surface made of EPDM rubber granules is  
colourfast and long-term UV-resistant (sun).



#### Toxicologically safe

No impermissible pollutant emissions,  
initial rubber odour dissipates over time.



#### Suitable for chlorinated water

Good resistance to chlorinated water,  
chlorinated cleaning agents and swimming pool  
water.

### Comparative values

The comparison of technical data on a scale from 1 to 5 provides a practical way of objectively comparing the relevant properties of WARCO products, making it easier to find the most suitable product for the intended application. Detailed information on the scale values and their calculation can be found online on the product detail page.

Compressive strength - Scale value 5 = approx. 0 mm residual dent  
after 24 hours of unloading (BS 7188)

Apparent density - scale value 5 = from 1000 kg/m<sup>3</sup>

Abrasion resistance – Resistance to abrasive wear – Scale value 3 =  
"very good" (BS 7188)

Thermal insulation – Scale value 5 = Thermal conductivity approx. 0.07  
W/(m·K)

Shock, vibration, and impact sound insulation – Scale value 5 =  
excellent damping

Water Permeability (EN 12616) – Rating 1 = Infiltration approx. 0 mm/h  
(0 l/h/m<sup>2</sup>)

**Michael Schladt**  
**WARCO Gulvbelægninger**  
Andergasse 17  
67434 Neustadt an der  
Weinstraße

WARCO Gallery  
Klemmhof 9  
67433 Neustadt an der Weinstraße  
Onsdag til fredag, 10:00 - 16:00

Faglig rådgivning  
+49 6321 9152391

E-mail: [info@warco24.dk](mailto:info@warco24.dk)  
Internet: [www.warco24.dk](http://www.warco24.dk)