



Dog Run Flooring (FF)

Dog Run Flooring Type FF consists of tiles made from rubber granules bonded with polyurethane. It is suitable for outdoor runs, halls and other indoor spaces. Each tile has two layers. The top consists of compacted finer granules. The coarser layer below carries the load and cushions impacts. The edges are bevelled, and the surface is grippy and slip-resistant, even when wet. The flooring is resilient, kind to paws, water-permeable and frost-resistant. It also insulates against cold from the substrate.

The tiles are laid in half bond using plastic connecting pins, with a firm edge restraint around the area. The substrate must be load-bearing, stable and largely level. Indoors, it must also tolerate moisture. On lawn, soil or gravel, gravel grids filled with chippings form the base. Water and urine pass through the tiles, then flow away down the gradient or soak into the ground. Half tiles for the edges are cut with a circular saw. A broom, garden hose or pressure washer is sufficient for cleaning.

Product data

Colour	Sand beige
Installation	Plastic connecting pins
External dimensions	500 x 500 x 30 mm


Weight	1 kg/
Net size when interlocked	50 x 50 x 3 cm 0,25 m²

Properties



Colour Sand beige

A light, neutral sand tone, Sand beige looks warm and welcoming and blends into any surroundings. A pigmented binder in a sand colour binds the black rubber granules from end-of-life tyres and coats their surface. At certain points black may show through, depending on compaction. Sunlight may make a new surface look slightly warmer at first. Initial wear may produce a salt and pepper look. The coating may also be worn away completely under heavy use or over time.




Installation

Plastic connecting pins are cylindrical and have a profiled surface. They are fitted into factory-drilled holes on two opposite sides of each tile. The tiles are laid in a half-bond installation. Each tile is therefore connected by plastic connecting pins to two tiles in the preceding row and two in the following row. Across the pin axis, the pins restrain tile movement, but they do not restrain movement along the axis. The tiled area therefore requires a fixed edge restraint.



Material

The product has two layers: a visible wearing layer on top and a base layer beneath it. The wearing layer consists of fine to medium recycled rubber granules with a granule size of 0.5–2.5 mm, the base layer of coarse recycled rubber granules of 2–4 mm. In both layers, the granules are cleaned rubber recovered from end-of-life tyres (ELT), consisting of natural rubber (NR) and styrene-butadiene rubber (SBR). A PU binder is used in both layers, clear in the black and anthracite versions and pigmented in the coloured ones. The surface of the wearing layer is finely textured.



Underside

The underside is divided into square pads, with shallow drainage channels running between them in a right-angled grid. The channels run right to the edge and line up with those of the adjacent tiles. Outdoors and in damp environments, water can run along the channels, following the gradient. On a water-permeable sub-base it soaks away directly into the ground. Please refer to the installation instructions.

Dog Run Flooring (FF)

Properties



Harmful substance limits met

Meets EU limits for harmful substances. Initial rubber odour diminishes.



Frost-resistant

Tolerates frost and freezing pore water without bursting, cracking or breaking.



Critical fall height 110 cm (BS EN 1177)

Impact attenuating playground surfacing – certified safety surfacing for private and public play areas.



Indoor and outdoor use

Frost-resistant, suitable for indoor and outdoor use.



Efl

Normally flammable.



UV-stabilised

ELT granules are UV-stabilised. Some coating shades may change slightly outdoors.

Technical data

The key technical properties of WARCO products are rated on a scale of 1 to 5. This allows products intended for the same application to be compared directly. The relevant product page explains how each rating is determined.

Compressive strength – Rating 2: permanent indentation of approximately 0.75 mm after 24 hours' recovery (BS 7188)

Slip resistance (BS EN 16165) – Rating 4: mean acceptance angle approx. 16°, R10 classification

Abrasion resistance – Rating 4: very high (BS 7188)

Thermal insulation – Rating 3: thermal conductivity approximately 0.11 W/(m·K)

Dynamic friction class DS (BS EN 14041) – Rating 3: dynamic coefficient of friction approx. 0.45

Apparent density – Rating 1: up to 780 kg/m³

Shock absorption and vibration damping, footstep sound reduction – Rating 3: marked damping

Water permeability (BS EN 12616) – Rating 5: infiltration approx. 1,000 mm/h (1,000 l/(m²·h))

Michael Schladt WARCO Floor Coverings

Andergasse 17
67434 Neustadt an der
Weinstraße

WARCO Gallery
Klemmhof 9
67433 Neustadt an der Weinstraße
Wednesday to Friday, 10:00 to 16:00

Technical consultation

+49 6321 9152391

Email: info@warco.eu
Internet: www.warco.eu